

# Safety Data Sheet – Gauge Red



---

## Section 1: Product and Company Identification

---

**Product Identifier:** Gauge Red

**Product Names:** Gauge Red

**Product uses:** various industrial uses

**Manufacturer:**

Industrial Mineral Company  
7268 Frasinetti Road  
Sacramento, California 95828  
www.clayimco.com

**Emergency Telephone Number:** 916-383-2811

**Telephone Number for Information:** 916-383-2811

---

## Section 2: Hazards Identification

---



Carcinogen



Irritant (skin and eye)

Skin Sensitizer

Respiratory Tract Irritant

**OSHA/HCS status:** This naturally occurring clay is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

**Classification of the substance of mixture:** OSHA –Carcinogenicity (inhalation) - Category 1A and Specific organ toxicity (Repeated Exposure) (Respiratory tract through inhalation) – Category 1

**Exposure limits for Crystalline Silica:** The current American Conference of Government Industrial Hygienist Threshold limit value for crystalline silica is: 0.025 mg/m<sup>3</sup>

**Signal Word:** Danger

**Hazard Statement** Cancer Hazard. Contains quartz (crystalline silica) which may cause cancer. Risk of cancer depends upon duration and level of exposure to the dust. Not an acute hazard. Prolonged inhalation of dust may cause lung injury. Inhalation of high concentrations of dust may cause mechanical irritation and discomfort of the respiratory tract. Repeated exposure may have chronic effects. Can cause skin, respiratory, and eye irritation.

**Precautionary Statement:** Wear protective gloves, eye, and respiratory protection. Avoid breathing dust.

---

## Section 3: Composition Information

---

Natural occurring material exact chemical composition varies.

Chemical Name		CAS Number	approximate %
Quartz (Silica)	SiO <sub>2</sub>	14808-60-7	18
Kaolinite	Al <sub>2</sub> Si <sub>2</sub> O <sub>5</sub> (OH) <sub>4</sub>	1318-74-7	70
Mica/Illite	(K,Na,Ca)(Al,Mg,Fe) <sub>2</sub> (Si,Al) <sub>4</sub> O <sub>10</sub> (OH,F) <sub>2</sub>	12001-26-2	<5
Hematite	Fe <sub>2</sub> O <sub>3</sub>	1317-60-8	13

# Safety Data Sheet – Gauge Red



Smectite	$(Ca,Na)_x(Al,Mg,Fe)_4(Si,Al)_8O_2(OH)_4 \bullet H_2O$	12199-37-0	<5
----------	--	------------	----

## Section 4: First-Aid Measures

**Eye Contact:** If eye contact occurs, rinse immediately with plenty of water. If irritation persists, seek medical attention

**Skin Contact:** Wash thoroughly with water. If irritation persists, seek medical attention

**Inhalation:** Move victim to fresh air in well ventilated area. If coughing or irritation persists, seek medical attention

**Ingestion:** Consult physician and/or obtain competent medical assistance

## Section 5 Fire Fighting Measures

**General Fire Hazards:** Not flammable

**Extinguishing Media:** Use appropriate extinguishing media for surrounding fire

**Special Fire Fighting Procedure:** None

## Section 6: Accidental Release Measures

**Clean-up Methods:** When dust is generated it may over expose cleanup personnel to dust. Using respirators or wetting the material is recommended. When dry sweeping use NIOSH approved respirators when dust levels exceed exposure limits

**Personal Precautions and Personal Protective Equipment:** Wear appropriate protective equipment and clothing during clean-up. If dusty conditions exist use approved respirators.

**Environmental Precautions:** Material is a natural mineral product and will not cause adverse effects to the water system other than turbidity from suspended particles.

## Section 7: Handling and Storage

**Handling Procedures:** Wear the appropriate eye protection and avoid dust contact with eyes. Minimize dust generation and accumulation. Wear the appropriate respiratory protection when in poorly ventilated areas. Use good industrial hygiene practices.

## Section 8: Exposure Controls/Personal Protection

### Airborne Exposure Limits:

#### Silica component limit

CAL OSHA PEL: TWA 0.05 mg/m<sup>3</sup> (respirable)

ACGIH TLV: TWA 0.025 mg/m<sup>3</sup> (respirable)

NIOSH REL: TWA 0.05 mg/m<sup>3</sup> (respirable)

#### Kaolinite component limit

OSHA PEL: TWA 5 mg/m<sup>3</sup> (respirable)

OSHA PEL: TWA 15 mg/m<sup>3</sup> (total dust)

CAL OSHA PEL: TWA 15 mg/m<sup>3</sup> (total dust)

# Safety Data Sheet – Gauge Red



## Mica component limit

OSHA PEL: TWA 3 mg/m<sup>3</sup> (respirable)

OSHA PEL: TWA 20 mppcf

## Hematite component limit (Same as Iron Oxide Dust)

OSHA PEL: TWA 5 mg/m<sup>3</sup> (respirable)

OSHA PEL: TWA 15 mg/m<sup>3</sup> (total dust)

CAL OSHA PEL: TWA 5mg/m<sup>3</sup>

## Smectite component limit

OSHA PEL: TWA 5 mg/m<sup>3</sup> (respirable)

OSHA PEL: TWA 15 mg/m<sup>3</sup> (total dust)

**Engineering Measures:** Use local exhaust ventilation to control exposure below component limits when dust creation is likely

## Personal Protective Equipment (PPE):

**Respiratory:** Avoid actions that cause dust exposure to occur. Use local or general ventilation to control exposures below applicable exposure limits. NIOSH or MSHA approved particulate filter respirators should be used. Respirator and/or filter cartridge selection should be based on the ANSI Standard Z88.2.

**Eyes:** When working around activities where dust can contact the eyes, wear safety glasses or goggles to avoid eye irritation or injury. Wearing contacts without sealing goggles is not recommended.

**Skin and Body:** Protective Clothing is not essential

---

## Section 9: Physical and Chemical Properties

---

<b>Appearance:</b> Red	<b>Odor:</b> none
<b>Physical state:</b> Powder	<b>Odor threshold:</b> No data Available
<b>pH:</b> no data available	<b>Flashpoint:</b> NA
<b>Melting/Freezing Point:</b> no data available	<b>Boiling Point:</b> NA
<b>Evaporation Rate:</b> NA	<b>Flammability:</b> Not Flammable
<b>Vapor Pressure (mm HG):</b> 0 (approximately)	<b>Vapor Density:</b> NA
<b>Relative density:</b> NA	<b>Specific Gravity:</b> No data available
<b>Solubility in water at 100 C:</b> 0 (approximately)	<b>Partition coefficient:</b> No data available
<b>Decomposition temperature:</b> no data available	<b>Auto-ignition temperature:</b> NA
<b>Viscosity:</b> NA	

---

## Section 10: Stability and Reactivity

---

**Reactivity:** No dangerous reactions are known under normal conditions of use

**Chemical Stability:** Stable

**Possibility of Hazardous Reactions and Conditions to Avoid:** None known

**Incompatibility:** None Known

# Safety Data Sheet – Gauge Red



---

## Section 11: Toxicological Information

---

### Possible Health Effects:

**Target Organs:** Skin, Eyes, and Respiratory system

**Exposure Routes:** Inhalation, skin or eye contact

### Effects:

**Short Term Exposure:** Shortness of breath and/or coughing associated with dust inhalation.

**Long Term Exposure (Chronic):** Steady and prolonged exposure to dust concentrations high than LTV without approved respirator could cause silicosis, a chronic disease of the lungs marked by acute fibrosis, may cause cancer based on animal data.

### Effects of Silicosis

Bronchitis/chronic obstructive Pulmonary Disorder

Increased susceptibility to Tuberculosis

Scleroderma

Possible Renal

### Symptoms of Silicosis

Shortness of breath, fever fatigue, loss of appetite, chest pain, dry non-productive cough, respiratory failure, death.

OSHA, IARC, and NTP Carcinogen Classifications				
Chemicals with recognized Carcinogen Potential	CAS#	OSHA	IARC	NTP
Quartz (Crystalline Silica)	14808-60-7	Yes	Yes – Group 1	Yes
Iron Oxide Dust (Hematite)	1317-60-8	No	No- Group 3	No

---

## Section 12: Ecological Information

---

**Eco toxicity:** None Known

**Biochemical oxygen demand (BOD5):** None known

**Chemical oxygen demand (COD):** None known

**Products of Biodegradation:** None known

**Toxicity of the products of biodegradation:** None known

**Bioaccumulation Potential:** None known

**Potential to move from soil to groundwater:** None Know

**Other adverse effects:** None known

---

## Section 13: Disposal Considerations

---

**Personal Protection:** Refer to section 8 for proper PPE when disposing of waste material

**Appropriate disposal containers:** No special requirements

**Appropriate disposal methods:** Disposal of this product should comply with the requirements of environmental protection and waste disposal legislation and any regional or local authority requirements.

**Physical and chemical properties that may affect disposal:** Dust should be minimized in disposal by either transporting in seal containers or wetting dust before transport

# Safety Data Sheet – Gauge Red



**Sewage disposal:** do not dispose of into sewage systems, material will settle out of water and clog pipes.  
**Special precautions for landfills or incineration activities:** None

---

## Section 14: Transport Information

---


Regulatory Information	UN Number	UN Proper Shipping Name	Transport Hazard Class	Packing Group Number	Bulk Transport Guidance	Special Precautions
DOT Classification	Not Regulated	-	-	-	-	-
TDG Classification	Not Regulated	-	-	-	-	-
ADR/RID Class	Not Regulated	-	-	-	-	-
IMDG Class	Not Regulated	-	-	-	-	-
IATA-DGR Class	Not Regulated	-	-	-	-	-

---

## Section 15 Regulatory Information

---

**TSCA – Toxic Substances Control Act – EPA** Quartz and other chemicals are listed in the TSCA Chemical Substance Inventory

 **WARNING:** This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**SARA/Title III (Emergency Planning & Community Right-to-Know Act)** This mixture contains no substances at or above the reporting threshold under section 313, based on available data.

---

## Section 16: Other Information

---

### Definitions

**ASTM** – American System of Testing and Materials

**OSHA** – Occupational Safety & Health Administration

**IARC** – International Agency for Research on Cancer

**NTP** – National Toxicogmail.com

**HCS** – Hazardous Communication Standard

**CAS** – Chemical Abstract Service

**ACGIH** – American Conference of Governmental Industrial Hygienists

**CAL-OSHA** – California Occupational Safety & Health Administration

**OSHA PEL** – OSHA Permissible Exposure Levels

**OSHA STEL** - spot exposure for a duration of 15 minutes, which cannot be repeated more than 4 times per day with at least 60 minutes between exposure periods.

**TLV** – Threshold Limit Value

**TWA** – Time Weighted Average

# Safety Data Sheet – Gauge Red



**TLV-TWA** –Time weighted average Threshold limit value

**TLV-STEL** – Short-term exposure limit Threshold limit value

**TLV-C** – Ceiling Limit – absolute limit that should not be exceeded at any time

Revisions: Existing MSDS revised to new GHS format. Revision Date 08/28/2015

Updated 3/29/19 silica exposure limits and Prop 65 language

The information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so, nothing here in is to be construed as recommending any practice or product in violation of any patent, law, or regulation. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material we supply.