

Distributed by: Laguna Clay Company 14400 Lomitas Ave City of Industry, CA 91746 1-800-4Laguna info@lagunaclay.com www.lagunaclay.com

Ferro Corporation Performance Pigments & Colors 251 West Wylie Ave. Washington, PA 15301 USA

Emergency telephone number CHEMTREC: 1-800-424-9300

CHEMTREC (outside U.S.): 1-703-527-3887

Phone Number: 1-724-223-5900

Date of Preparation: 09/14/2011

MATERIAL SAFETY DATA SHEET

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name: 41776A Black Spersastain

DRM100LB

Inorganic Pigment Chemical Family:

CAS-No.: Mixture **Product Code:** 1133488

2. HAZARDS IDENTIFICATION

Emergency Overview

Caution

May cause respiratory tract, eye and skin irritation. Avoid dust formation. May cause physical irritation.

		HIVIS	NFPA /04
Color:	Black	1	1
Physical state:	Powder	0	0
Odor:	Odorless	0	0
343	000000	Ε	

Potential Health Effects

Principle routes of exposure: Inhalation, ingestion, skin and eye contact.

May cause slight irritation. Eye contact:

Skin contact: Prolonged skin contact may cause skin irritation and/or dermatitis.

May cause irritation of respiratory tract. Inhalation:

Ingestion: May irritate digestive tract.

Chronic toxicity: No known effects under normal conditions of use. Excessive inhalation of dust may cause

chemical pneumonitis, cyanosis, and pulmonary edema. Chronic inhalation exposure can

cause lung damage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Weight %
Hematite, chromium green black	68909-79-5	95 - 99%
Silica, fumed	112945-52-5	1 - 5%

4. FIRST AID MEASURES

Rinse immediately with plenty of water, also under the eyelids. Get medical attention if irritation Eye contact:

develops.

Skin contact: Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing

before re-use. If symptoms persist, call a physician.

Laguna Clay Company 1-800-4Laguna info@Lagunaclay.com www.Lagunaclay.com

Product name: 41776A Black Spersastain DRM100LB Page 1 of 4 Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

Ingestion: Drink plenty of water. Do not induce vomiting. Consult a physician if necessary.

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash point (°C): Non combustible

Suitable extinguishing media: Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment. The product itself does not burn.

Hazardous decomposition products: Metal fumes.

Special protective equipment for

firefighters:

As in any fire, wear self-contained breathing apparatus (pressure-demand, NIOSH approved or

equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Avoid dust formation. Evacuate area of all unnecessary personnel. Avoid contact with skin,

eyes and clothing. Wear personal protective equipment. Ensure adequate ventilation.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Do not flush

into surface water or sanitary sewer system. Prevent product from entering drains.

Methods for cleaning up: Wear personal protective equipment. Sweep up and shovel into suitable containers for

disposal. Clean contaminated surface thoroughly. Dispose of promptly.

7. HANDLING AND STORAGE

Handling:

Handle in accordance with good industrial hygiene and safety practice. Avoid dust formation. Avoid contact with skin, eyes and clothing. Wash hands thoroughly before eating, drinking or smoking. In case of insufficient ventilation, wear suitable respiratory equipment. Provide appropriate exhaust ventilation at places where dust is formed.

Storage:

Keep container tightly closed in a dry and well-ventilated place. Store in original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits

Minimize exposure in accordance with good hygiene practice.

Components	OSHA	ACGIH
Hematite, chromium green black	0.5 mg/m ³ TWA Cr	0.5 mg/m³ TWA Cr

Engineering measures: Provide appropriate exhaust ventilation at machinery and at places where dust or fumes can

be generated. Ensure adequate ventilation, especially in confined areas.

Eye protection: Safety glasses with side-shields.

Skin and body protection: Lightweight protective clothing.

Hand protection: Impervious gloves.

Respiratory protection: Use NIOSH approved respirator when ventilation is inadequate. NIOSH-approved respirators

should be worn where engineering controls and work practices do not reduce exposure to or below the PEL. In case of insufficient ventilation wear suitable respiratory equipment. Seek

professional advise prior to respirator selection and use.

Laguna Clay Company www.Lagunaclay.com 1-800-4Laguna info@Lagunaclay.com

Product name: 41776A Black Spersastain DRM100LB Page 2 of 4

Hygiene measures: Wash hands before breaks and at the end of workday. Contaminated work clothing should not

be allowed out of the workplace. Ensure that eyewash stations and safety showers are

proximal to the work-station location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color: Black Physical state: Powder

Odor: Odorless Molecular weight: No data available No data available No data available Boiling point/range (°C): pH: Melting point/range (°C): No data available Specific gravity (Water =1): No data available Non-volatile Vapor pressure: No data available Vapor density:

Evaporation Rate (Water = 1) Non-volatile Water solubility: Insoluble

VOC content (%) 0

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Polymerization Will not occur.

Hazardous decomposition products: None under normal use.

Materials to avoid: None known.

Conditions to avoid None known.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Information given is based on data on the components and the toxicology of similar products

Carcinogenic Effects: Not listed by IARC, NTP or OSHA as a carcinogen.

Target Organ Effects: Chromium compound (inorganic): Eyes, skin, respiratory system.

Component information, if any, is listed below

Silica, fumed

LD50s and LC50s: Oral LD50 (Rat) = 3160 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic toxicity: No data is available on the product itself. Information given is based on data on the

components and the ecotoxicology of similar products.

Persistence and degradability: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused

products:

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Where possible recycling is preferred to disposal or incineration.

ations, where possible recycling is preferred to disposal of incideratio

14. TRANSPORT INFORMATION

DOT (U.S.)

Proper shipping name: Not regulated.

TDG (Canada)

Proper shipping name: Not regulated.

Laguna Clay Company www.Lagunaclay.com 1-800-4Laguna info@Lagunaclay.com

14. TRANSPORT INFORMATION

15. REGULATORY INFORMATION

U.S. Regulations:

TSCA: Not subject to TSCA 12(b) Export Notification

SARA 313:

Components	U.S CERCLA/SARA - Section 313 - Emission Reporting
Chromium compounds (40 - 50%)	1.0 % de minimis concentration

State Regulations

This product or its ingredients have been evaluated for New Jersey, Pennsylvania, and California Prop 65 supplier notification requirements. Substances that are subject to notification requirements, if any, are listed below.

Components	PARTK:
Chromium compounds	Listed (PARTK)

Components	NJRTK:
Chromium compounds	Listed (NJRTK)

Canadian WHMIS

WHMIS hazard class: D28 Toxic materials

Canadian Ingredient Disclosure List (IDL):

Canadian ingredient disclosure List (IDL).	
Components	Canada - WHMIS Ingredient Disclosure:
Chromium compounds	0.1

International Inventories

TSCA 8(b): Listed or exempt.

Canadian DSL/NDSL list All ingredient(s) are listed on the DSL or NDSL

EC-No. Listed or exempt.

Philippines (PICCS): Listed.

Japan (ENCS): Listed or exempt.

Korea (KECL): Listed.

China (IECS): One or more ingredient(s) are not on the IECS list.

Australia (AICS): Listed.
New Zealand (NZIoC): Listed.

16. OTHER INFORMATION

For Industrial Use Only.

Prepared by: Ferro Technical Center

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.

End of Safety Data Sheet