

# MATERIAL SAFETY DATA SHEET

PRODUCT: Powder REVISION DATE: 09/27/2007 REVISION NUMBER: 2 Date Printed: 09/27/2007

## 1. PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: Ferro Corporation

251 West Wylie Avenue

P.O. Box 519

Washington, PA 15301 Prod Info 724-223-5900 CHEMTREC 800-424-9300

Use the CHEMTREC telephone number only in the event of chemical emergencies.

PREPARED BY: Mike Pellegrini

**Environmental Engineer** 

PRODUCT CODE: TR1132

PRODUCT TRADE NAME: TR1132 FRIT

**CAS NO:** 65998-18-4\*

CHEMICAL FAMILY: Decorative Coating PRODUCT TYPE: Glass Enamel/Flux

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

This product does not have exposure limit values. Exposure limit values for some of the components are listed below as a guideline for safe use of this product.

#### **HAZARDOUS COMPONENTS**

INGREDIENTS/CAS#	OSHA PEL:	ACGIH TLV:
Borates	NE	TWA 1.0 mg/m <sup>3</sup>
Proprietary		-
Crystalline Silica	TWA (Total Dust): 30 mg/m <sup>3</sup> / (%Quartz + 2)	TWA: Respirable Fraction: 0.05 mg/m <sup>3</sup>
14808-60-7	TWA (Resp. Frt): 250 mppcf / (%Quartz + 5)	
	STEL (Resp. Frt.): 10 mg/m <sup>3</sup> / (%Quartz + 2)	
Lead Compound	TWA as Pb: 0.05 mg/m <sup>3</sup>	TWA as Pb: 0.05 mg/m <sup>3</sup>
NONE		-

# 3. HAZARDS IDENTIFICATION

PRINCIPLE ROUTES OF EXPOSURE: Inhalation, ingestion and dermal.

### The key immediate hazards are:

Skin, eye, and respiratory irritant

### **Effects from Acute Exposure:**

**EYE CONTACT:** Causes eye irritation.

Ferro Corporation Page 1 of 6

**SKIN CONTACT:** Causes skin irritation.

**INHALATION:** Causes lung irritation.

**INGESTION:** May be harmful if swallowed.

#### AGGRAVATED MEDICAL CONDITIONS:

Respiratory

Populations at increased risk to lead include individuals with one kidney removed, persons genetically predisposed to kidney dysfunction, individuals with genetically caused glucose-6-phosphate dehydrogenase deficiency, individuals with hemoglobin S or O or Thalassemia.

### **Effects from Chronic Exposure:**

### **CARCINOGENIC INGREDIENTS:**

The International Agency for Research on Cancer (IARC) has determined that lead and inorganic lead compounds are possible human carcinogens.

### **OVEREXPOSURE EFFECTS:**

### **CONTAINS BOROSILICATE FRIT:**

Overexposure to borosilicate frit may cause skin, eye, and respiratory irritation due to the physical nature of the particulates. Repeated and prolonged breathing of these particulates might cause coughing, wheezing, impaired lung function, and increased sputum production. Smoking aggravates these effects.

### **CONTAINS LEAD COMPOUNDS:**

Acute overexposure to lead is relatively infrequent and occurs from swallowing lead compounds or inhaling lead vapors. Symptoms include a bitter or metallic taste in the mouth, dry throat, thirst, stomach pain, nausea and vomiting. Muscle weakness, pain and leg cramps, headache, insomnia, depression, coma, and death are possible. The kidney may also be damaged.

Chronic lead overexposure can result in anemia, kidney damage and encephalopathy. Encephalopathy is characterized by headache, insomnia, vomiting, visual disturbances, irritability, restlessness, convulsion, and coma. Recovery is slow and frequently incomplete. These effects are directly related to blood lead levels.

# 4. FIRST AID MEASURES

**INGESTION:** If swallowed, give at least 3-4 glasses of water, but do not induce vomiting. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention.

**SKIN:** For skin contact, wash affected areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

**INHALATION:** If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.

Ferro Corporation Page 2 of 6

**EYES:** For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical attention if irritation develops.

**NOTES TO PHYSICIAN:** Use of this product is regulated by the OSHA Lead Standard (29 CFR 1910.1025). The extensive medical surveillance and worker removal provisions of this standard should be consulted. Lead and its inorganic compounds are neurotoxins which may produce peripheral neuropathy.

## 5. FIRE FIGHTING MEASURES

**OSHA FLAMMABILITY CLASS: NON-COMBUSTIBLE** 

FLASH POINT (°F): Not Applicable

Lower Explosive Limit: Not Applicable

**Upper Explosive Limit:** Not Applicable

**EXTINGUISHING MEDIA: Water** 

**FIRE FIGHTING PROCEDURES:** Fire-Fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires.

Use water spray to cool nearby containers and structures exposed to fire.

**UNUSUAL HAZARDS:** This product will not burn. Use appropriate techniques for fighting surrounding fire.

### 6. ACCIDENTAL RELEASE MEASURES

**SPILL PROCEDURES:** Wear appropriate protective equipment. Avoid the generation of dust. Collect material and place in closable container(s) for disposal.

Dry sweeping of lead containing dust is a violation of the OSHA Lead Standard (29 CFR 1910.1025). For clean up of lead containing products, HEPA (high efficiency particulate air purifying) filtered vacuuming equipment or equally effective filtration methods shall be used and emptied in a manner that minimizes re-entry of lead into the workplace.

# 7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Avoid contact with eyes, skin and clothing.

**NOTES ON HANDLING INFORMATION:** Minimize dust generation during handling. Use adequate ventilation.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ferro Corporation Page 3 of 6

**VENTILATION:** Adequate ventilation should be provided to keep concentrations below acceptable Exposure Limits. Discharge from the ventilation system should comply with the applicable air pollution control regulations.

If air from exhaust ventilation is recirculated into the workplace, the system shall have a high efficiency filter and be monitored to assure effectiveness in accordance with the OSHA Lead Standard (29 CFR 1910.1025).

**EYE PROTECTION:** Wear safety glasses or goggles to protect against exposure.

**PROTECTIVE GLOVES:** Use gloves as a standard industrial handling procedure.

**RESPIRATORY PROTECTION:** Appropriate respiratory protection is required when exposure to airborne contaminant is likely to exceed acceptable limits. Respirators should be selected and used in accordance with OSHA Subpart I (29 CFR 1910.134) and manufacturer's recommendations.

OTHER PERSONAL PROTECTIVE EQUIPMENT: None specified.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** White Powder

**BOILING POINT: Not Applicable** 

VAPOR DENSITY (AIR=1): Non-Volatile

EVAP. RATE(BUTYL ACETATE=1): Non-Volatile

VOC, Wt.% (EPA METH.24): 0

**BULK DENSITY: Not Available** 

SOLUBILITY (in water): Insoluble

## 10. STABILITY AND REACTIVITY

**STABILITY DATA: STABLE** 

**POLYMERIZATION: WILL NOT OCCUR** 

**HAZARDOUS DECOMPOSITION PRODUCTS:** None known.

**INCOMPATIBILITY** 

(MATERIALS TO AVOID): None known.

CONDITIONS/HAZARDS TO AVOID: None known.

## 11. TOXICOLOGICAL INFORMATION

No Toxicological data known.

## 12. ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION:** No data at this time

Ferro Corporation Page 4 of 6

CHEMICAL FATE INFORMATION: No data at this time. PERSISTENCE/DEGRADABILITY: No data at this time.

**APPRAISAL:** No data at this time. **MOBILITY:** No data at this time.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL OF WASTE METHOD:** Dispose in accordance with Federal, State and Local regulations.

### 14. TRANSPORT INFORMATION

**DOT Shipping Name: NON-HAZARDOUS** 

**DOT HAZARD CLASS: NONE** 

DOT LABEL(S): NONE UN/NA NUMBER: NONE PACKING GROUP: NONE

## 15. REGULATORY INFORMATION

SARA SECTION 302: None Found

SARA (311, 312) HAZARD CLASS: ACUTE HEALTH HAZARD

CHRONIC HEALTH HAZARD

#### SARA 313 Title III Toxic Chemical List:

The following chemicals are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

100 % Lead, inorganic 33 % Metal as Pb

**TSCA Inventory Status:** This product (and/or all of its components) is in compliance with the U.S. EPA Toxic Substance Control Act, TSCA, (15 U.S.C. 2604).

This product and all of its components is listed on the DSL inventory.

## 16. OTHER INFORMATION

Revisions: The Format has been changed to meet the requirements of the new ANSI Standard Z400.1.

Ferro Corporation Page 5 of 6

#### LABEL INFORMATION:

WARNING!

Skin, eye, and respiratory irritant.

Avoid contact with eyes, skin and clothing.

Avoid breathing dust.

Keep away from food products.

Wash thoroughly after handling and before eating, drinking or using cosmetic or tobacco products or toilet facilities.

Use with adequate ventilation.

Keep container closed when not in use.

Contains lead which may cause blood, gastrointestinal, nervous and reproductive effects.

Handle in accordance with the OSHA Lead Standard.

FIRST AID: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water. Remove contaminated clothing. Get medical attention.

IN CASE OF FIRE: Use water, dry chemical or carbon dioxide.

IN CASE OF SPILL: Collect and dispose in accordance with federal, state and local regulations.

FOR INDUSTRIAL USE ONLY.

#### **DEFINITIONS AND ABBREVIATIONS:**

ACGIH = American Conference of Governmental Industrial Hygienists

C (CEIL) = The concentration that shall not be exceeded during any part of the working exposure.

CAS # = Chemical Abstracts Service Registry Number

EPA = Environmental Protection Agency

IARC = International Agency for Research on Cancer

NIOSH = National Institute for Occupational Safety and Health

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

PEL = Permissible Exposure Limit

SARA = Superfund Amendments and Reauthorization Act

STEL = Short Term Exposure Limit. Usually a 15 minute time weighted average exposure.

TLV = Threshold Limit Values

TSCA = Toxic Substance Control Act

TWA = Time Weighted Average. Exposure concentration for a normal 8 hour day or 40 hour week.

VOC = Volatile Organic Content

**DISCLAIMER:** The information contained in this Material Safety Data Sheet (MSDS) has been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No guarantee is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine the regulatory compliance obligations under any applicable federal or state laws.

\*\*\* END OF MSDS \*\*\*

Ferro Corporation Page 6 of 6