



Missouri Grog
 Missouri Calcined Fireclay, Calcined Flint Clay, Calcined
 Fire clay, STKO®, Calcined plastic, Calcined plastic fire
 clay, Calcined Flint, Dust Collector Fines



Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 06/06/2013

Version: 1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Identifier

Product Form: Mixture

Product Name: Missouri Calcined Fireclay, Calcined Flint Clay, Calcined Fire clay, STKO®, Calcined plastic, Calcined plastic fire clay, Calcined Flint, Dust Collector Fines

Intended Use of the Product

Use of the Substance/Mixture: High temperature aggregates

Name, Address, and Telephone of the Responsible Party

Christy Minerals LLC
 833 Booneslick Rd.
 High Hill, MO 63350
 T (636)585-2214
christyco.com

Distributed by:
 Laguna Clay Company
 14400 Lomas Ave
 City of Industry, CA 91746
 1-800-4Laguna
info@lagunaclay.com
www.lagunaclay.com

Emergency Telephone Number

Emergency Number : 1-800-535-5053 Domestic, 1-352-323-3500 International

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS-US Classification

Carc. 1A H350
 STOT RE 1 H372

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS08

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H350 - May cause cancer (inhalation)
 H372 - Causes damage to organs through prolonged or repeated exposure (inhalation)

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P260 - Do not breathe dust.
 P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P280 - Wear protective gloves, protective clothing, eye protection, respiratory protection.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P314 - Get medical advice and attention if you feel unwell.
 P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards Not available

Unknown Acute Toxicity (GHS-US): Not available

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Mixture

Name	Product Identifier	% (w/w)	GHS-US Classification
Mullite	(CAS No) 1302-93-8	45 - 65	Not classified
Silica, amorphous	(CAS No) 7631-86-9	20 - 45	Not classified
Silica, cristobalite	(CAS No) 14464-46-1	4 - 15	Carc. 1A, H350 STOT RE 1, H372
Quartz	(CAS No) 14808-60-7	0 - 7	Carc. 1A, H350 STOT RE 1, H372
Titanium dioxide	(CAS No) 13463-67-7	0 - 2.75	Not classified

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. If exposed or concerned: Get medical advice/attention

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation persists

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

Ingestion: Rinse mouth. Do NOT induce vomiting. Seek medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes damage to organs through prolonged or repeated exposure (inhalation).

Inhalation: May cause cancer by inhalation. Dust from this product may cause irritation to the respiratory tract.

Skin Contact: Prolonged contact with large amounts of dust may cause mechanical irritation.

Eye Contact: Prolonged contact with large amounts of dust may cause mechanical irritation.

Ingestion: If a large quantity has been ingested: intestinal blockage. Gastrointestinal irritation.

Chronic Symptoms: Repeated or prolonged exposure to respirable crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Not available

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Avoid generating dust.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Avoid generation of dust during clean-up of spills.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Vacuum must be fitted with HEPA filter to prevent release of particulates during clean-up. Avoid generation of dust during clean-up of spills.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Do not breathe dust. Avoid dust production. Repeated or prolonged exposure to respirable crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands, forearms, and other exposed areas thoroughly after handling

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Avoid generation of dust. Keep container closed when not in use.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Specific End Use(s)

High temperature aggregates

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Quartz (14808-60-7)		
Mexico	OEL TWA (mg/m ³)	0.1 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	0.1 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³
Nunavut	OEL TWA (mg/m ³)	0.3 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	0.3 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	0.10 mg/m ³ (designated substance regulation)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³
Québec	VEMP (mg/m ³)	0.1 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³
Yukon	OEL TWA (mg/m ³)	300 particle/mL

Titanium dioxide (13463-67-7)

Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³

Silica, amorphous (7631-86-9)

USA NIOSH	NIOSH REL (TWA) (mg/m ³)	6 mg/m ³
USA IDLH	US IDLH (mg/m ³)	3000 mg/m ³
Nunavut	OEL TWA (mg/m ³)	0.15 mg/m ³ (regulated under Silica flour, total mass)
Northwest	OEL TWA (mg/m ³)	0.15 mg/m ³ (total mass, regulated under Silica flour)

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Territories		
Yukon	OEL TWA (mg/m ³)	2 mg/m ³
Silica, cristobalite (14464-46-1)		
Mexico	OEL TWA (mg/m ³)	0.05 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³
USA IDLH	US IDLH (mg/m ³)	25 mg/m ³
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	0.05 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³
Nunavut	OEL TWA (mg/m ³)	0.15 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	0.15 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	0.05 mg/m ³ (designated substance regulation)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³
Québec	VEMP (mg/m ³)	0.05 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³
Yukon	OEL TWA (mg/m ³)	150 particle/mL

Exposure Controls

Appropriate Engineering Controls: Provide adequate ventilation to minimize dust concentrations. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Respiratory protection of the dependent type. Protective clothing. Protective goggles. Gloves.



Materials for Protective Clothing: Chemically resistant materials and fabrics

Hand Protection: Protective gloves

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of dust are expected to exceed exposure limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: White - grey, dry aggregate to powder
Odor	: Odorless
Odor Threshold	: Not available
pH	: 6 - 8

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: > 1500 °C (2732°F)
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 2.3-2.7 g/cc
Solubility	: Not available
Log Pow	: Not available
Log Kow	: Not available
Viscosity, Kinematic	: Not available
Viscosity, Dynamic	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not available
Explosion Data – Sensitivity to Static Discharge	: Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Stable at standard temperature and pressure.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products: Not available

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity : Not classified

LD50 and LC50 Data Not available

Skin Corrosion/Irritation: Not classified **pH: 6 - 8**

Serious Eye Damage/Irritation: Not classified **pH: 6 - 8**

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: May cause cancer (inhalation).

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs through prolonged or repeated exposure (inhalation).

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause cancer by inhalation. Dust from this product may cause irritation to the respiratory tract.

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Skin Contact: Prolonged contact with large amounts of dust may cause mechanical irritation.

Symptoms/Injuries After Eye Contact : Prolonged contact with large amounts of dust may cause mechanical irritation.

Symptoms/Injuries After Ingestion: If a large quantity has been ingested: intestinal blockage. Gastrointestinal irritation.

Chronic Symptoms: Repeated or prolonged exposure to respirable crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
Silica, amorphous (7631-86-9)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat (mg/l)	> 2.2 mg/l (Exposure time: 1 h)
Quartz (14808-60-7)	
IARC Group	1
National Toxicity Program (NTP) Status	2
Titanium dioxide (13463-67-7)	
IARC Group	2B
National Toxicity Program (NTP) Status	1
Silica, amorphous (7631-86-9)	
IARC Group	3
Silica, cristobalite (14464-46-1)	
IARC Group	1

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Silica, amorphous (7631-86-9)	
LC50 Fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)
EC50 Other Aquatic Organisms 1	440 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)

Persistence and Degradability

Missouri Calcined Fireclay, Calcined Flint Clay, Calcined Fire clay, STKO®, Calcined plastic, Calcined plastic fire clay, Calcined Flint, Dust Collector Fines	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Missouri Calcined Fireclay, Calcined Flint Clay, Calcined Fire clay, STKO®, Calcined plastic, Calcined plastic fire clay, Calcined Flint, Dust Collector Fines	
Bioaccumulative Potential	Not established.
Silica, amorphous (7631-86-9)	
BCF fish 1	(no bioaccumulation expected)

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

UN Number Not regulated for transport

UN Proper Shipping Name Not regulated for transport

Additional Information Not regulated for transport

Transport by Sea Not regulated for transport

Air Transport Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
--	--

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Silica, amorphous (7631-86-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Mullite (1302-93-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Silica, cristobalite (14464-46-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
--	--

Titanium dioxide (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
--	--

Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Titanium dioxide (13463-67-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Silica, amorphous (7631-86-9)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Silica, cristobalite (14464-46-1)
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Canadian Regulations

Missouri Calcined Fireclay, Calcined Flint Clay, Calcined Fire clay, STKO®, Calcined plastic, Calcined plastic fire clay, Calcined Flint, Dust Collector Fines

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	---



Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.
Listed on the Canadian Ingredient Disclosure List

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--

Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--

Silica, amorphous (7631-86-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.
Listed on the Canadian Ingredient Disclosure List

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

Mullite (1302-93-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Silica, cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.
Listed on the Canadian Ingredient Disclosure List

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION

Indication of Changes : 06/06/2013
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H335	May cause respiratory irritation
H350	May cause cancer
H351	Suspected of causing cancer

Missouri Calcined Fire Clay, Calcined Flint Clay, Calcined Fire clay, STKO, Calcined plastic, Calcined plastic fire clay

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H372	Causes damage to organs through prolonged or repeated exposure
------	--

Party Responsible for the Preparation of This Document

Christy Minerals LLC
833 Booneslick Rd.
P.O. Box 159
High Hill, MO 63350
(636)585-2214

The Christy Minerals L.L.C. has taken reasonable care preparing these materials and believes the information and recommendations to be accurate as of the date of issue. We make no representation, warranty or guarantee as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy itself as to the suitability and completeness of such information for its own particular use. Christy Minerals L.L.C. will not be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information.

This information is supplied to be informative and to alert the user of the material. The ultimate compliance with federal, state, and/or local regulations concerning the use of this material, or compliance with respects to products liability, rest solely upon the purchaser thereof. Christy Minerals and STKO are registered trademarks belonging to Christy Minerals and its affiliates and subsidiaries registered in the U.S.

North America GHS US 2012 & WHMIS