## MATERIAL SAFETY DATA SHEET

Resco Products, Inc. Prepared By: **Research & Development** Telephone No: **Penn Center West** 336-299-1441 Ext. 20

**Building 2, Suite 430** Date: 08/14/13 Pittsburgh, PA 15276 Supersedes Date: 09/14/10

Emergency Telephone No.: 412-494-4491

Section 1- Product Name

**Alumina-Silicate Mineral** Material Name:

Intended Use: **Mineral Grain** 

Product Name: Pyrotrol All Grades (2253, 2254, 3503)

Brand Code: 0268, 0723, 0269

Section 2- Composition and Information On Hazardous Ingredients					
Ingredient	CAS No.	% Weight	OSHA PEL	ACGIH TLV	SEC 313
Crystalline Silica (Total)	Not Applicable	40-70	Not Applicable	Not Applicable	No
Cristobalite	14464-46-1		0.05 mg/m <sup>3</sup> Respirable	0.025mg/m <sup>3</sup> Respirable	
Tridymite	15468-32-3		0.05 mg/m <sup>3</sup> Respirable	Withdrawn	
Quartz	14808-60-7		0.1 mg/m <sup>3</sup> Respirable	0.025mg/m <sup>3</sup> Respirable	

Notes: (1) The PEL and TLV values shown above are 8-hour time-weighted averages, unless otherwise specified.

### Section 3- Hazards Identification

Emergency Overview: No unusual fire or spill hazard. Dust may be irritating to skin, eyes, and mucous membranes.

Primary Route(s) of Entry for Particulate: Eye: Yes Skin: Yes inhalation: Yes Ingestion: No

**Potential Adverse Health Effects:** 

	Adverse Health Ellevier				
Acute:	Eye: May irritate and/or abrade eyes.				
	Skin: None known.				
	Inhalation: Dust of this product may be irritating to respiratory tract.				
Chronic:	Eye: None known.				
	Skin: None known.				
	Inhalation: Prolonged or repeated inhalation of dusts of this product in excess of the stated PEL or TLV				
	may cause lung disease (Silicosis). According to the International Agency for Research on Cancer (IARC),				
	there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of				
	quartz or cristobalite from occupational sources.				

Carcinogenicity: Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1, NTP).

California Proposition 65: This product contains crystalline silica, a chemical known to the State of California to cause

Signs and Symptoms of Overexposure: Coughing can result from overexposure to dust.

Medical Conditions Generally Aggravated by Exposure to Particles: Pre-existing diseases or other conditions of the lungs, skin, eyes, and mucous membranes.

### Section 4- First Aid Measures

Eye Contact: Flush product from eyes using large amounts of water, if irritation continues, seek medical attention.

**Skin Contact:** Wash product from skin using soap and water, if irritation continues, seek medical attention.

Inhalation: If exposed to excessive levels of dust remove victim to fresh air. Seek medical attention if coughing or other symptoms persist.

**Ingestion:** As shipped, product is not likely to be ingested, but if it occurs, do not induce vomiting. Seek medical attention.

## Section 5- Fire Fighting Measures

Flash Point: Not Applicable

Flammable Limits: Not Applicable

**LEL:** Not Applicable **UEL:** Not Applicable

Autoignition Temperature: Not Applicable

**Extinguishing Media:** As appropriate for surrounding fire. **Fire Fighting Instructions:** As appropriate for surrounding fire.

Fire Fighting Equipment: Fire fighters should wear NIOSH approved, positive pressure, self-contained breathing

apparatus (SCBA) and full protective clothing (bunker gear) when fighting fires.

**Hazardous Combustion Products: None** 

Flame Propagation or Burning Rate of Solid Material: Not Applicable

Flammability Classification (As defined by 29 CFR 1910.1200): Not Flammable

**Product Name: Pyrotrol All Grades** 

### Section 6- Accidental Release Measures

If dusts are generated during the spill, these should be collected by gently sweeping the material into a dust pan or collecting with a vacuum device. All personnel engaged in cleanup operations should adhere to the instructions outlined in section 8 for personal protection. Disposal of wastes from cleanup operations should be carried out in accordance to the guidelines outlined in Section 13.

# Section 7- Handling and Storage

Handling: Avoid direct contact with product or dust from product by wearing protective clothing, using approved respiratory protection, and wearing gloves of the impermeable type.

Storage: The product should be stored in a dry location. Pallet protection such as shrink-wrap or stretch-wrap should be kept in place until the product is required for installation.

# Section 8- Exposure Control/Personal Protection

Engineering Controls: Process enclosures, local exhaust ventilation, or other engineering process controls may be necessary to keep any air contaminates associated with this product within their TLV's. This is particularly true if the user operation generates dust, vapors, or mist.

Respiratory Protection: Since this product is a proprietary mixture of unique ingredients, it does not have an established limit for airborne concentration (PEL or TLV), which workers can routinely be exposed to without suffering adverse health effects. This MSDS is prepared to alert customers and other users to the various components of the product and their relative quantity and toxicity in the product as provided. The user must review his/her own circumstances and then determine what is required to establish a respiratory protection program that meets OSHA 1910.134 requirements. If workplace conditions warrant respiratory protection, use MSHA/NIOSH approved units as listed in the current 29 CFR 1910.134 for the existing conditions. Some type or respiratory protection is recommended even for the best conditions. Actual respirator selection should be made after consultation with a competent health and safety professional.

**Eye Protection:** Industrial-type safety glasses offer some protection, goggles offer more.

Protective Gloves: Use as needed to prevent direct skin contact.

Other Protective Clothing or Equipment: Wear clothing designed to limit direct exposure to product, or dust, vapors, or mist associated with product. If clothing becomes contaminated, it should be laundered before wearing again. Maintain good personal hygiene. Wash hands thoroughly before eating or drinking.

Section 9- Physical and Chemical Properties		
Appearance: Granular Powder, Earthy Color	Vapor Pressure (mm Hg): Not Applicable	
Odor: Earthy Odor	Vapor Density: Not Applicable	
Water solubility: Slight	pH: Not Determined	
<b>Density (H<sub>2</sub>O=1):</b> 2.8	Boiling Point: Not Applicable	
% Volatile (By Weight@ 1800°F): 0 Melting Point: Greater than 2000°F		
Section 10- Stability and Reactivity		

Chemical Stability: This product is stable under normal conditions of shipping, storage, and installation.

Conditions to Avoid: None **Incompatible Materials:** None Hazardous Decomposition: None Hazardous Polymerization: None

Reactivity: None			
	Sect	tion 11- Toxicological Information	
	LD <sub>50</sub>	LC <sub>50</sub>	
Crystalline Silica (Total)			
Cristobalite	No Data	No Data	
Tridymite	No Data	No Data	
Quartz	No Data	No Data	
Target Organs			
Crystalline Silica (Total)			
Cristobalite	Respiratory		
Tridymite	Respiratory		
Quartz	Respiratory		
Long Term Toxicity			
Crystalline Silica (Total)			
Cristobalite	Repeated and prolong	jed inhalations may cause lung disease (silicosis).	
Tridymite	Repeated and prolonged inhalations may cause lung disease (silicosis).		
Quartz	Repeated and prolonged inhalations may cause lung disease (silicosis).		
Short Term Toxicity			
Crystalline Silica (Total)			
Cristobalite	Repeated and prolong	jed inhalations may cause lung disease (silicosis).	

Date: 08/14/13

**Product Name: Pyrotrol All Grades** 

Tridymite	Repeated and prolonged inhalations may cause lung disease (silicosis).
Quartz	Repeated and prolonged inhalations may cause lung disease (silicosis).

## Section 12- Ecological Information

Accidental Release: No information has been developed regarding the ecotoxicity or environmental fate of this product.

## Section 13- Disposal Considerations

Waste Disposal Method: The as manufactured refractory, or dust from this material, is not considered a hazardous waste as defined by 40 CFR 261. However, used product (and dust generated during maintenance and tear-out operations) may be contaminated with other hazardous substances from the particular application (for example, metals). Therefore, appropriate waste analysis may be necessary to determine proper disposal. Waste characterization and disposal/treatment methods should be determined by a qualified environmental professional in accordance with applicable federal, state, and local regulations.

# Section 14-Transport Information

DOT (Department of Transportation) Classification under 49 CFR 172.101: Not Regulated

**UN (United Nations) Number:** Not Applicable **NA (North American) Number:** Not Applicable

# Section 15- Regulatory Information

Resco Products, Inc. considers this product to be hazardous as defined by the OSHA Hazardous Communications Standard (29 CFR 1910.1200). Section 2 chemicals, which must be addressed, and the summary of regulatory and other lists upon which they appear are:

INGREDIENT	CAS NUMER	LIST
Crystalline Silica	Not Applicable	
Cristobalite	14464-46-1	1,2,3,4
Tridymite	15468-32-3	2,3,4
Quartz	14808-60-7	1,2,3,4

The lists are as follows:

- 1. ACGIH TLV "Threshold Limit Values" (2013)
- 2. OSHA Air Contaminates- Permissible Exposure Limits
- 3. Canadian Domestic Substance List
- 4. EPA TSCA Chemical Inventory List

WHMIS Hazard Classification (Canada): D-2A

SARA Title III: Section 311/312 Hazardous Categories: Irritant

### Section 16- Other Information

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein; however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.



Distributed by:
Laguna Clay Company
14400 Lomitas Ave
City of Industry, CA 91746
1-800-4Laguna
info@lagunaclay.com
www.lagunaclay.com

Date: 08/14/13